

TECHNICAL SPECIFICATIONS

Length overall	13.61 m (44'8")
Max. beam	4.17 m (13'8")
Max. Beam (with open balconies)	5.52 m (18'1")
Max. draft	0.72 m (29")
Light craft mass	8,700 kg (19,200 lbs)
Deadrise angle	20°
Fresh water capacity	275 L (70 US Gal)
Fuel capacity (inboards)	1100 L (290 Gal)
Fuel capacity (outboards)	1650 L (435 US Gal)
Bridge clearance	3.35 m (11')
Passenger capacity (day)	14
Passenger capacity (night)	4
Designer	Marcio Schaefer

CONSTRUCTION

Vacuum infusion GRP with PVC foam coated hull, deck and superstructure Isophthalic gel coat Skin coat in estervinílic resin Structural stringers with girder and floor plate

STANDARD FEATURES

COCKPIT

Hard top Glass windshield with wiper Sofa in weather resistant upholstery Table with coasters Gourmet area with sink, faucet and ice box Electric grill Navigation lights Head lights Radar arch lights Mast Light 12V LED Courtesy Lights Hydraulic balconies

HELM STATION

Command seat for three persons Engine control display Control of interior and navigation lights Control of pumps and ventilation of the engine room Control of winch and wipers Compass

STERN

Built-in stainless-steel ladder with hand grip Hand-held Shower Cockpit stern safety gates

BOW

Stainless steel rail Sunbathing cushion

CABIN / LOUNGE

Furniture with shelves and drawers Staircase with wooden steps Bow sofa convertible into double bed Mid-ship twin bed with a filler cushion for double bed Carpet Air conditioning 12 V LED courtesy lights





GALLEY

Refrigerator Silestone® countertop with sink and faucet Furniture with shelves 2-burner electric cockpit Microwave oven

HEAD

Full electric toilet Sink and Faucet Enclosed Shower

LIGHTING

12V LED lights

MOORING SYSTEM

6 stainless steel cleats Windlass with local and remote control Anchor, swivel and chain

ENGINE ROOM

POWER SUPPLY

7.5 kW generator 50 Amp inlet

BILGE PUMP SYSTEM

2 x 2000 GPH 12V electric bilge pump with automatic switch and manual switch option Flood alarm system

BATTERIES

2 x 150 Ah 12V DC batteries for engines (1 battery per engine, parallel system) 2 x 220Ah 12V DC batteries for service 60A 12V Battery Charger

OTHER EQUIPMENT

50 / 60A Galvanic Isolator Hot water system Holding tank Soundproofing Exhaust fans Electric trim tabs

